



★ VDS Specifications

Model (Cascade Refresh)	VDS-5050	VDS-6550	VDS-7550	VDS-R-G530	VDS-R-G630
Dimension	800(L)x448(W)x90(H)mm	800(L)x448(W)x90(H)mm	800(L)x448(W)x90(H)mm	800(L)x448(W)x90(H)mm	800(L)x448(W)x90(H)mm
CPU	2*Intel(R) Xeon(R) Processor Silver 4210R 10c 2.4GHz	2*Intel(R) Xeon(R) Processor Silver 4214R 12c 2.4GHz	2*Intel(R) Xeon(R) Processor Gold 6226R 16c 2.9GHz	2*Intel(R) Xeon(R) Processor Gold 6226R 16c 2.9GHz	2*Intel(R) Xeon(R) Processor Gold 6244 8c 3.6GHz
Memory Type	DDR4	DDR4	DDR4	DDR4	DDR4
Memory	128G (4*32G)	192G (6*32G)	256G (8*32G)	128G (4*32G)	128G (4*32G)
Memory Slots	24 slots, max support 32G per slot	24 slots, max support 32G per slot	24 slots, max support 32G per slot	24 slots, max support 32G per slot	24 slots, max support 32G per slot
	System disk 2*128G			System disk 1*128G	
Hard Drive	3 options available: 1. Intel 240G (Minimum configuration) 2. Intel 480G 3. Intel 960G (Minimum ONE disk, prohibit to deliver the server WITHOUT caching disk.)	3 options available: 1. Intel 240G (Minimum configuration) 2. Intel 480G 3. Intel 960G (Minimum ONE disk, prohibit to deliver the server WITHOUT caching disk.)	3 options available: 1. Intel 240G (Minimum configuration) 2. Intel 480G 3. Intel 960G (Minimum ONE disk, prohibit to deliver the server WITHOUT caching disk.)	3 options available: 1. Intel 240G*2 (Minimum configuration) 2. Intel 480G*2 3. Intel 960G*2 (Minimum caching capacity 480G) (Minimum TWO disk, prohibit to deliver the server with one caching disk or without caching disk.)	3 options available: 1. Intel 240G*2 (Minimum configuration) 2. Intel 480G*2 3. Intel 960G*2 (Minimum caching capacity 480G) (Minimum TWO disk, prohibit to deliver the server with one caching disk or without caching disk.)
	Data disk is optional (quantity is minimum 2, and recommended as even number)				
Disk Slots	12 * front 2.5/3.5"	12 * front 2.5/3.5"	12 * front 2.5/3.5"	8 * front 2.5/3.5"	8 * front 2.5/3.5"
Max. Storage Capacity in Single Disk Slot for Data Disk	8T				
NIC	6*GE+2*10GE optical ports	6*GE+2*10GE optical ports	6*GE+2*10GE optical ports	6*GE+2*10GE optical ports	6*GE+2*10GE optical ports
PCIe Type	PCIe 3.0	PCIe 3.0	PCIe 3.0	PCIe 3.0	PCIe 3.0
Total PCIe Slot	5	5	5	6	6
Spare PCIe Slot	2	2	2	3	3
Supported Network Card	2*10GE Optical port card (Original factory) 2*GE port card (Original factory)	2*10GE Optical port card (Original factory) 2*GE port card (Original factory)	2*10GE Optical port card (Original factory) 2*GE port card (Original factory)	2*10GE Optical port card (Original factory) 2*GE port card (Original factory)	2*10GE Optical port card (Original factory) 2*GE port card (Original factory)
GPU	Not Support			Option: Light load: M10*1 or M10*2 Moderate or heavy load: T4*1 or T4*2	Option: Light load: M10*1 or M10*2 Moderate or heavy load: T4*1 or T4*2
IO Port	2*USB2.0 2*USB3.0 1*VGA	2*USB2.0 2*USB3.0 1*VGA	2*USB2.0 2*USB3.0 1*VGA	2*USB2.0 4*USB3.0 1*VGA	2*USB2.0 4*USB3.0 1*VGA
Serial Port	1				
PSU	550W or 800W dual PSU	550W or 800W dual PSU	800W dual PSU	1600W dual PSU	1600W dual PSU



Model	VDS-E1900
Dimension	800 (L) x 448 (W) x 90 (H) mm
CPU	1*Intel® Core™ i9 Processors 8c 3.60GHz
Memory Type	DDR4
Memory	64G (4*16G)
Memory Slots	4 slots
Hard Drive	System disk 128G (occupied one front disk slot)
	Caching disk is optional (Minimum one disk)
	Data disk is optional (quantity is minimum 2, and recommended as even number)
Disk Slots	8 * front 2.5/3.5"
Max. storage capacity in single disk slot for data disk	8T
NIC	4*GE
PCIe type	PCIe 3.0
Occupied PCIe Slot	0
Spare PCIe Slot	2 (X8)
Supported Network Card	4*GE port card (Original factory)
GPU	Not Support
IO Port	2*USB3.0 4*USB2.0 1* VGA
Serial Port	Not Support
PSU	550 Dual PSU

Sangfor All-Inclusive Hyper-Converged Solution





★ VDC Specifications

Model	VDC-2500	VDC-2600	VDC-4600	VDC-8500
Memory	4GB	4GB	8GB	8GB
Storage Capacity	64GB SSD	64GB SSD	64GB SSD	64GB SSD
Operating Temperature	0-45 °C	0-45 °C	0-45 °C	0-45 °C
PSU	40W (Max)	40W (Max)	60W (Max)	150W (Max)
Power Supply Redundancy	N	N	Y	Y
GE Electrical Ports	6	6	6	6
GE Optical Port SFP	/	/	4	4
10GE Optical Port SFP+	/	/	/	2
Serial Port (RJ45)	1			
USB Port	2			
Dimension	375 (L) * 430 (W) * 44.5 (H) mm	375 (L) * 430 (W) * 44.5 (H) mm	400 (L) * 430 (W) * 44.5 (H) mm	600 (L) * 440 (W) * 89 (H) mm
Net Weight	3.85KG	3.85KG	4.5KG	12.95KG



★ Thin-Client Specifications

Model	Hardware Specification	Port	Dimensions (mm)	Power (w)	Weight (kg)	Scenario
STD-500	Intel x86 CPU, 2*cores 2.41GHz, 2G memory, 16G storage, USB*6 (2*USB 3.0), 1GE port*1, Dual Audio port*1	1*VGA + 1*HDMI	170 * 110 * 31	15	0.52	1. 3D Enterprise Design 2. 2D Desktop Dual Screen 3. 3D Desktop Dual Screen
STD-200H-S (VGA)	ARM A9 CPU, 4*cores 1.6GHz, 1G memory, 4G storage, USB*6, Dual Audio port*1, 100M Ethernet port*1	1*VGA	170 * 105 * 29	7	0.35	1. General Office 2. Education Scenario 3. Manufacturing 4. Call Center
STD-200H-S (HDMI)	ARM A9 CPU, 4*cores 1.6GHz, 1G memory, 4G storage, USB*6, Dual Audio port*1, 100M Ethernet port*1	1*HDMI	170 * 105 * 29	7	0.35	