



★ Intel Broadwell CPU

Model	VDS-3550	VDS-5050	VDS-6550	VDS-P-G320	VDS-P-G620
Dimension	800 (L) x 446 (W) x 89 (H) mm	800 (L) x 446 (W) x 89 (H) mm	800(L)x446(W)x89(H)mm	712 (L) x 440 (W) x 89 (H) mm	712 (L) x 440 (W) x 89 (H) mm
CPU	2*Intel(R) Xeon(R) Processor E5-2620 V4 8c 2.10GHz	2*Intel(R) Xeon(R) Processor E5-2630 V4 10c 2.20GHz	2*Intel(R) Xeon(R) Processor E5-2640 V4 10c 2.40GHz	2*Intel(R) Xeon(R) Processor E5-2640 V4 10c 2.40GHz	2*Intel(R) Xeon(R) Processor E5-2667 V4 8c 3.20GHz
Memory Type	DDR4	DDR4	DDR4	DDR4	DDR4
Memory	96G (3*32G)	128G (4*32G)	160G (5*32G)	160G (5*32G)	160G (5*32G)
Memory Slots	20 slots, max support 32G per slot	20 slots, max support 32G per slot	20 slots, max support 32G per slot	24 slots, max support 32G per slot	24 slots, max support 32G per slot
Hard Drive	System Disk 64G			System Disk 128G	
	Caching disk 150G (Minimum one disk)	Caching disk 240G (Minimum one disk)	Caching disk 240G (Minimum one disk)	3 options available: 1.Intel 240G*2(Minimum configuration) 2.Intel 480G*2 3.Intel 960G*2 Minimum caching capacity 480G (Minimum two disk, prohibit to deliver the server with one caching disk or without caching disk.)	3 options available: 1.Intel 240G*2(Minimum configuration) 2.Intel 480G*2 3.Intel 960G*2 Minimum caching capacity 480G (Minimum two disk, prohibit to deliver the server with one caching disk or without caching disk.)
	Data disk is optional (quantity is minimum 2, and recommended as even number)				
Disk Slots	2 * rear (inside) 2.5" 8 * front 2.5/3.5"	2 * rear (inside) 2.5" 8 * front 2.5/3.5"	2 * rear (inside) 2.5" 8 * front 2.5/3.5"	2 * rear 2.5" 2 * front 2.5" 6 * front 3.5"	2 * rear 2.5" 2 * front 2.5" 6 * front 3.5"
Max. storage capacity in single disk slot for data disk	8T				
NIC	6*GE	6*GE	6*GE	2*10GE (electrical) + 4*GE	2*10GE (electrical) + 4*GE
GPU	Not Support			NVIDIA Tesla M10*1	Option: Light load: M10*1 or M10*2 Moderate or heavy load: M60*1 or M60*2
IO Port	3*USB3.0 1* VGA	3*USB3.0 1*VGA	3*USB3.0 1*VGA	5*USB3.0 1*front VGA 1*rear VGA	5*USB3.0 1*front VGA 1*rear VGA
Serial Port	Located on the back of the chassis				
PSU	550W single PSU	550W dual PSU	550W dual PSU	1300W dual PSU	1300W dual PSU

**★ Intel Skylake CPU**

Model	VDS-3550	VDS-5050	VDS-6550	VDS-G530	VDS-G630
Dimension	801.2 (L) x 448 (W) x 87.8 (H) mm	801.2 (L) x 448 (W) x 87.8 (H) mm	801.2 (L) x 448 (W) x 87.8 (H) mm	760 (L) x 448 (W) x 87 (H) mm	760 (L) x 448 (W) x 87 (H) mm
CPU	2*Intel(R) Xeon(R) Processor Silver 4110 8c 2.1GHz	2*Intel(R) Xeon(R) Processor Silver 4114 10c 2.2GHz	2*Intel(R) Xeon(R) Processor Gold 5115 10c 2.4GHz	2*Intel(R) Xeon(R) Processor Gold 6132 14c 2.6GHz	2*Intel(R) Xeon(R) Processor Gold 6136 12c 3.0GHz
Memory Type	DDR3	DDR4	DDR4	DDR4	DDR4
Memory	96G (3*32G)	128G (4*32G)	160G (5*32G)	160G (10*16G)	160G (10*16G)
Memory Slots	24 slots, max support 32G per slot	20 slots, max support 32G per slot	24 slots, max support 32G per slot	24 slots, max support 32G per slot	24 slots, max support 32G per slot
Hard Drive	System Disk 64G			System Disk 128G	
	3 options available: 1.Intel 240G(Minimum configuration) 2.Intel 480G 3.Intel 960G Minimum ONE disk	3 options available: 1.Intel 240G(Minimum configuration) 2.Intel 480G 3.Intel 960G Minimum ONE disk	3 options available: 1.Intel 240G(Minimum configuration) 2.Intel 480G 3.Intel 960G Minimum ONE disk	3 options available: 1.Intel 240G*2(Minimum configuration) 2.Intel 480G*2 3.Intel 960G*2 Minimum TWO disk	3 options available: 1.Intel 240G*2(Minimum configuration) 2.Intel 480G*2 3.Intel 960G*2 Minimum TWO disk
	Data disk is optional (quantity is minimum 2, and recommended as even number)				
Disk Slots	2 * rear (inside) 2.5" 8 * front 2.5/3.5"	2 * rear (inside) 2.5" 8 * front 2.5/3.5"	2 * rear (inside) 2.5" 8 * front 2.5/3.5"	2 * rear (inside) 2.5" 8 * front 2.5/3.5"	2 * rear (inside) 2.5" 8 * front 2.5/3.5"
Max. storage capacity in single disk slot for data disk	8T				
NIC	6*GE	6*GE	6*GE	6*GE	6*GE
GPU	Not Support			Option: Light load: M10*1 or M10*2 Moderate or heavy load: M60*1 or M60*2	Option: Light load: M10*1 or M10*2 Moderate or heavy load: M60*1 or M60*2
IO Port	2*USB2.0 (Front) 2*USB3.0 (Rear) 1* rear VGA	2*USB2.0 (Front) 2*USB3.0 (Rear) 1* rear VGA	2*USB2.0 (Front) 2*USB3.0 (Rear) 1* rear VGA	2*USB2.0 (Front) 2*USB3.0 (Rear) 1* rear VGA 1* front VGA	2*USB2.0 (Front) 2*USB3.0 (Rear) 1* rear VGA 1* front VGA
Serial Port	Located on the back of the chassis				
PSU	550W single PSU	550W dual PSU	550W dual PSU	1600W dual PSU	1600W dual PSU



★ VDC Hardware

Model	VDC-2500	VDC-2600	VDC-4500	VDC-4600	VDC-8500
Memory	2GB	4GB	4GB	8GB	8GB
Storage Capacity	64GB SSD	64GB SSD	64GB SSD	64GB SSD	64GB SSD
Operating temperature	0-40 °C	0-45 °C	0-40 °C	0-40 °C	0-60 °C
PSU	60W (Max)	250W (Max)	350W (Max)	350W (Max)	300W (Max)
Power Supply Redundancy	N	N	N	Y	
GE ports	4	6	6	6	4
Optical Port SFP	/	/	2	4	4
Serial port (RJ45)	1				
USB Port	2				
Dimension	300(L) * 430(W) * 44.5(H) mm	390(L) * 430(W) * 44.5(H) mm	600(L) * 440(W) * 89(H) mm	600(L) * 440(W) * 89(H) mm	600(L) * 440(W) * 89(H) mm
Net Weight	4KG	6.65KG	15.3KG	15.3KG	15.4KG



★ Thin-Client

Model	Hardware Specification	Port	Dimensions (mm)	Power (w)	Weight (kg)	Scenario
STD-500	Intel Celeron N2807 CPU, 2*cores 1.58GHz, 2G memory, 8G storage, USB*6 (1*USB 3.0), 1GE port*1, Dual Audio port*1	1*VGA + 1*HDMI	170 * 110 * 31	15	0.52	1. 2D Desktop Dual Screen 2. 3D Desktop Dual Screen
STD-200H (VGA)	ARM A9 CPU, 4*cores 1.6GHz, 1G memory, 4G storage, USB*6, Audio port*1	1*VGA	128 * 128 * 28	7	0.35	1. General Office 2. Education Scenario 3. Manufacturing 4. Call Center 5. 3D Enterprise Design
STD-200H (HDMI)	ARM A9 CPU, 4*cores 1.6GHz, 1G memory, 4G storage, USB*6, Audio port*1	1*HDMI	128 * 128 * 28	7	0.35	